

GRAPHICS - Wide Format Ink Jet Print Media

 Issue date : 05/01/2005
 Date last modification : 09/12/2016

4-GL3C-04060 RI-JET TRANSLUCENT WHITE ASP30 REMOVABLE WK135

Face Material

Translucent white polymeric vinyl.

Type	Polymeric vinyl	
Colour and Finish	Translucent white	
Weight	120 g/m ² ±10%	ISO-536
Thickness	90 µ ±10%	ISO 534-80

Adhesive

Solvent based semipermanent adhesive featuring high water resistance. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	ASP30 semipermanent	
Type	Acrylic semipermanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-30°C/+100°C	
Shear	Medium	
Tack	High N/inch ²	
Final Adhesion	Medium N/inch	

Liner

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	135 g/m ² ±10%	PP-032 - ISO 536
Thickness	145 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Luminous trasmittance in according to DIN EN 166/169/170 is 36,6%.

For advertising and promotional applications (outdoor and indoor posters, billboards and signs) and for vehicle applications (flat sided including buses, trams and taxis). Particularly suitable for illuminated signs and window graphics.

Printing Methods

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS:**

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

